

## Technical Datasheet

**Description:** Contour Satin Chrome Switched Fused Spur with Flex Outlet (White Insert/Matching Switch)

**Part Number:** CSC256



## Information

|                                |                                                                                                                                                           |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Plate Dimensions (mm)</b>   | 85 (W) x 85 (H) x 8 (D)                                                                                                                                   |
| <b>Insert Material</b>         | Polycarbonate                                                                                                                                             |
| <b>Earth Strap</b>             | Mild Steel                                                                                                                                                |
| <b>Operating Voltage(AC)</b>   | 250V @ 50Hz                                                                                                                                               |
| <b>Termination Type</b>        | Screw                                                                                                                                                     |
| <b>Warranty</b>                | 10 years                                                                                                                                                  |
| <b>Product Class 1</b>         | Must be earthed                                                                                                                                           |
| <b>Maintenance</b>             | Clean with a soft cloth only. Do not use a cleaning agent of any description.                                                                             |
| <b>Style</b>                   | Rounded Profile                                                                                                                                           |
| <b>Plate Material</b>          | Chrome Plated Solid Brass, Hand-finished, Lacquered                                                                                                       |
| <b>Switch Material</b>         | Metal                                                                                                                                                     |
| <b>Required back box depth</b> | 25mm                                                                                                                                                      |
| <b>Load Rating</b>             | 13A                                                                                                                                                       |
| <b>Switch type</b>             | Double pole                                                                                                                                               |
| <b>Terminal Capacity</b>       | 3x 2.5mm <sup>2</sup> ,3x 4.0mm <sup>2</sup> , 2x 6.0mm <sup>2</sup> (L&N) / 3x 2.5mm <sup>2</sup> ,2x 4.0mm <sup>2</sup> , 1x 6.0mm <sup>2</sup> (EARTH) |
| <b>Standards</b>               | BS 1363                                                                                                                                                   |
| <b>IP Rating</b>               | IP2XD                                                                                                                                                     |