

# G+H Electrical Accessories

## Technical Datasheet



**Description:** Deco Polished Brass Double Socket with USB  
(White Switches)

**Part Number:** DB910W



## Information

|                                |                                                                               |
|--------------------------------|-------------------------------------------------------------------------------|
| <b>Plate Dimensions (mm)</b>   | 153 (W) x 95 (H) x 8 (D)                                                      |
| <b>Insert Material</b>         | Polycarbonate                                                                 |
| <b>Earth Strap</b>             | Mild Steel                                                                    |
| <b>Operating Voltage(AC)</b>   | 250V @ 50Hz                                                                   |
| <b>Termination Type</b>        | Screw                                                                         |
| <b>Warranty</b>                | 10 years                                                                      |
| <b>Product Class 1</b>         | Must be earthed                                                               |
| <b>Maintenance</b>             | Clean with a soft cloth only. Do not use a cleaning agent of any description. |
| <b>Please Note</b>             | Do not use masking tape on this product.                                      |
| <b>Style</b>                   | Stepped Slope Profile                                                         |
| <b>Plate Material</b>          | Solid Brass, Hand-finished, Lacquered                                         |
| <b>Switch Material</b>         | Polycarbonate                                                                 |
| <b>Required back box depth</b> | 25mm                                                                          |
| <b>Load Rating</b>             | 13A                                                                           |
| <b>Switch type</b>             | Double pole                                                                   |
| <b>Terminal Capacity</b>       | 3x 2.5mm <sup>2</sup> ,3x 4.0mm <sup>2</sup> , 2x 6.0mm <sup>2</sup>          |
| <b>Standards</b>               | BS 1363, BS EN 62368                                                          |
| <b>IP Rating</b>               | IP2XD                                                                         |