



Information

|                         |                                                                                                                                                            |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Plate Dimensions (mm)   | 86 (W) x 145 (H) x 2 (D)                                                                                                                                   |
| Insert Material         | Polycarbonate                                                                                                                                              |
| Earth Strap             | Mild Steel                                                                                                                                                 |
| Operating Voltage(AC)   | 250V @ 50Hz                                                                                                                                                |
| Termination Type        | Screw                                                                                                                                                      |
| Warranty                | 10 years                                                                                                                                                   |
| Product Class 1         | Must be earthed                                                                                                                                            |
| Maintenance             | Clean with a soft cloth only. Do not use a cleaning agent of any description.                                                                              |
| Please Note             | Do not use masking tape on this product.                                                                                                                   |
| Style                   | Flat Profile                                                                                                                                               |
| Plate Material          | Mild Steel, Powder Coated                                                                                                                                  |
| Switch Material         | Metal                                                                                                                                                      |
| Required back box depth | 47mm                                                                                                                                                       |
| Load Rating             | 45A                                                                                                                                                        |
| Switch type             | Double pole                                                                                                                                                |
| Terminal Capacity       | 4x 4.0mm <sup>2</sup> ,3x 6.0mm <sup>2</sup> , 1x 16.0mm <sup>2</sup> (L&N) / 3x 2.5mm <sup>2</sup> ,2x 4.0mm <sup>2</sup> , 1x 6.0mm <sup>2</sup> (EARTH) |
| Standards               | BS EN 60669-1, BS 4177(sockets)                                                                                                                            |
| IP Rating               | IP2XD                                                                                                                                                      |