

Description: Flat Rose Gold Switched Fused Spur with Flex Outlet (Black Switch)

Part Number: FRG56B



Information

|                         |                                                                               |
|-------------------------|-------------------------------------------------------------------------------|
| Plate Dimensions (mm)   | 86 (W) x 86 (H) x 2 (D)                                                       |
| Insert Material         | Polycarbonate                                                                 |
| Earth Strap             | Mild Steel                                                                    |
| Operating Voltage(AC)   | 250V @ 50Hz                                                                   |
| Termination Type        | Screw                                                                         |
| Warranty                | 10 years                                                                      |
| Product Class 1         | Must be earthed                                                               |
| Maintenance             | Clean with a soft cloth only. Do not use a cleaning agent of any description. |
| Please Note             | Do not use masking tape on this product.                                      |
| Style                   | Flat Profile                                                                  |
| Plate Material          | Solid Copper, Hand-finished, Lacquered                                        |
| Switch Material         | Polycarbonate                                                                 |
| Required back box depth | 35mm                                                                          |
| Load Rating             | 13A                                                                           |
| Switch type             | Double pole                                                                   |
| Terminal Capacity       | 3x 2.5mm² ,3x 4.0mm², 2x 6.0mm²(L&N) / 3x 2.5mm² ,2x 4.0mm², 1x 6.0mm²(EARTH) |
| Standards               | BS 1363                                                                       |
| IP Rating               | IP2XD                                                                         |