



Information

|                         |   |
|-------------------------|---|
| Plate Dimensions (mm)   | 94 (W) x 94 (H) x 8 (D)   |
| Insert Material         | Polycarbonate   |
| Earth Strap             | Mild Steel  |
| Operating Voltage(AC)   | 250V @ 50Hz   |
| Termination Type        | Screw   |
| Warranty                | 10 years  |
| Product Class 1         | Must be earthed   |
| Maintenance             | Clean with a soft cloth only. Do not use a cleaning agent of any description.   |
| Please Note             | Do not use masking tape on this product.  |
| Style                   | Stepped Profile with Rope edge  |
| Plate Material          | Solid Brass, Hand-finished, Lacquered   |
| Switch Material         | Polycarbonate   |
| Required back box depth | 25mm  |
| Load Rating             | 13A   |
| Switch type             | Double pole   |
| Terminal Capacity       | 3x 2.5mm <sup>2</sup> , 3x 4.0mm <sup>2</sup> , 2x 6.0mm <sup>2</sup> (L&N) / 3x 2.5mm <sup>2</sup> , 2x 4.0mm <sup>2</sup> , 1x 6.0mm <sup>2</sup> (EARTH) |
| Standards               | BS 1363   |
| IP Rating               | IP20D   |