



Information

|                         |  |
|-------------------------|--|
| Plate Dimensions (mm)   | 94 (W) x 154 (H) x 8 (D)   |
| Insert Material         | Polycarbonate  |
| Earth Strap             | Mild Steel   |
| Operating Voltage(AC)   | 250V @ 50Hz  |
| Termination Type        | Screw  |
| Warranty                | 10 years   |
| Product Class 1         | Must be earthed  |
| Maintenance             | Clean with a soft cloth only. Do not use a cleaning agent of any description.  |
| Please Note             | Do not use masking tape on this product.   |
| Style                   | Stepped Profile with Rope edge   |
| Plate Material          | Solid Brass, Hand-finished, Lacquered  |
| Switch Material         | Metal  |
| Required back box depth | 47mm   |
| Load Rating             | 45A  |
| Switch type             | Double pole  |
| Terminal Capacity       | 4x 4.0mm <sup>2</sup> , 3x 6.0mm <sup>2</sup> , 1x 16.0mm <sup>2</sup> (L&N) / 3x 2.5mm <sup>2</sup> , 2x 4.0mm <sup>2</sup> , 1x 6.0mm <sup>2</sup> (EARTH) |
| Standards               | BS EN 60669-1, BS 4177(sockets)  |
| IP Rating               | IP2XD  |